

SOLERA de COBRE para aplicaciones eléctricas

Equivalencias mm / pulgadas

Aleación C-1100

Largo 3.66 mts

Temple: Semi-duro

Norma: ASTM- B-187

| ESPESOR | ANCHO | PESO TEORICO (kg) |
|------------------|--------------------|-------------------|
| 1/8 " (3.175mm) | 1/2 " (12.7 mm) | 1,32 |
| 1/8 " (3.175mm) | 3/4 " (19.1 mm) | 1,98 |
| 1/8 " (3.175mm) | 1 " (25.4 mm) | 2,64 |
| 1/8 " (3.175mm) | 1-1/4 " (31.75 mm) | 3,29 |
| 1/8 " (3.175mm) | 1-1/2 " (38.1 mm) | 3,95 |
| 1/8 " (3.175mm) | 2 " (50.8 mm) | 5,25 |
| 3/16 " (4.76 mm) | 3/4 " (19.1 mm) | 2,96 |
| 3/16 " (4.76 mm) | 1 " (25.4 mm) | 3,94 |
| 3/16 " (4.76 mm) | 1-1/4 " (31.75 mm) | 4,93 |
| 3/16 " (4.76 mm) | 1-1/2 " (38.1 mm) | 5,91 |
| 3/16 " (4.76 mm) | 2 " (50.8 mm) | 7,89 |
| 3/16 " (4.76 mm) | 2-1/2 " (63.5 mm) | 9,9 |
| 3/16 " (4.76 mm) | 3 " (76.20 mm) | 11,83 |

| ESPESOR | ANCHO | PESO TEORICO (kg) |
|-----------------|--------------------|-------------------|
| 3/8 " (9.52 mm) | 2 " (50.8 mm) | 15,78 |
| 3/8 " (9.52 mm) | 2-1/2 " (63.5 mm) | 19,73 |
| 3/8 " (9.52 mm) | 3 " (76.20 mm) | 23,67 |
| 3/8 " (9.52 mm) | 3-1/2 " (88.9 mm) | 27,61 |
| 3/8 " (9.52 mm) | 4 " (101.6 mm) | 31,71 |
| 3/8 " (9.52 mm) | 5 " (127 mm) | 39,64 |
| 1/2 " (12.7 mm) | 1 " (25.4 mm) | 10,57 |
| 1/2 " (12.7 mm) | 1-1/2 " (38.1 mm) | 15,78 |
| 1/2 " (12.7 mm) | 1-3/4 " (44.45 mm) | 18,51 |
| 1/2 " (12.7 mm) | 2 " (50.8 mm) | 21,15 |
| 1/2 " (12.7 mm) | 2-1/2 " (63.5 mm) | 26,3 |
| 1/2 " (12.7 mm) | 3 " (76.20 mm) | 31,73 |
| 1/2 " (12.7 mm) | 3-1/2 " (88.9 mm) | 37,02 |

| ESPESOR | ANCHO | PESO TEORICO (kg) |
|------------------|--------------------|-------------------|
| 1/4 " (6.35 mm) | 1/2 " (12.7 mm) | 2,64 |
| 1/4 " (6.35 mm) | 3/4 " (19.1 mm) | 3,94 |
| 1/4 " (6.35 mm) | 1 " (25.4 mm) | 5,25 |
| 1/4 " (6.35 mm) | 1-1/4 " (31.75 mm) | 6,58 |
| 1/4 " (6.35 mm) | 1-1/2 " (38.1 mm) | 7,89 |
| 1/4 " (6.35 mm) | 2 " (50.8 mm) | 10,52 |
| 1/4 " (6.35 mm) | 2-1/2 " (63.5 mm) | 13,15 |
| 1/4 " (6.35 mm) | 3 " (76.20 mm) | 15,78 |
| 1/4 " (6.35 mm) | 3-1/2 " (88.9 mm) | 18,51 |
| 1/4 " (6.35 mm) | 4 " (101.6 mm) | 21,1 |
| 5/16 " (7.93 mm) | 1-1/2 " (38.1 mm) | 9,91 |
| 3/8 " (9.52 mm) | 1 " (25.4 mm) | 7,89 |
| 3/8 " (9.52 mm) | 1-1/2 " (38.1 mm) | 11,84 |

| ESPESOR | ANCHO | PESO TEORICO (kg) |
|-----------------|----------------|-------------------|
| 1/2 " (12.7 mm) | 4 " (101.6 mm) | 42,31 |
| 1/2 " (12.7 mm) | 5 " (127 mm) | 52,89 |
| 1/2 " (12.7 mm) | 6 " (152.4 mm) | 63,57 |
| 3/4 " (19.1 mm) | 4 " (101.6 mm) | 63,63 |

También disponible con recubrimiento de estaño. Posibilidad de suministro en medidas especiales.

| DETALLE DE LA ARISTA | FORMATOS |
|--|---------------------------------------|
| <p>Arista viva</p> <p>Arista matada</p> <p>Arista redondeada</p> | <p>Plano, en Rollo y Encarretado.</p> |